

# CLAMP ON TYRE

- No Contact with the rim
- Innovative Design for wheel quick positioning
- Reliable and fast clamping thanks to the innovative coupling mechanism



**HPA**  
Faip



**FEATURES**

- **Fastening to the wheel:** no contact with the rim to prevent any damage.
- **Quick:** quick lever-operated mounting and demounting, without toothed gears.
- **Self-centering:** the synchronous opening and closing mechanism allows the central pin to be always aligned with wheel centre. The rollers integrated inside jaws allow greater smoothness and mounting ease.
- **Runout:** suitable for thrust compensation procedure of 3D aligners (\*).
- **Lightweight and ergonomic:** the innovative design and low weight make it easy to handle and operate.

\* Refer to the wheel aligner catalogue to check for compatibility.

**OPTIONAL ACCESSORIES**

- Clamp holder multi-purpose trolley and additional jaws



- Clamp holder set for wall mounting with support for additional jaws



- Set of XL extensions for wheel diameter from 32" to 39"



- Extension set for use with vans

**TECHNICAL SPECIFICATIONS**

Compatibility	3D aligners (*)
Wheel diameter	19" to 39"
Rim diameter	10" to 30"

**Wheel arch protection included.**

The set of supplied extensible jaws allows working on wheel diameter from 19" to 32".

\* Refer to the wheel aligner catalogue to check for compatibility.



**NEXION S.p.A.**  
[www.hpa-faip.it](http://www.hpa-faip.it) - [info@hpa-faip.it](mailto:info@hpa-faip.it)

DPSF000544 02/2023